



Applications:

Replaces rigid tubing for supply water in swimming pool.

Properties:

Flexible PVC hose
Reinforced with shock resistant rigid PVC spiral
Easy assembly of fittings

Standart Colors:

Gray

Materials:

phthalate free
RoHS, Reach Standard
UV protection
Antibacterial additive

Temperatures Range:

-15°C < Temp <60°C

Standards:

ISO 1307
ISO 3994: 2007

| Code | External Diameter O.D. mm | Internal Diameter I.D. mm | Weight gr/m ± 10% | Working Pressure Bar / 20°C | Roll Length m |
|-----------|---------------------------|---------------------------|-------------------|-----------------------------|---------------|
| SPA-020GY | 20 | 16 | 160 | 7 | 25 |
| SPA-025GY | 25 | 19 | 220 | 7 | 25 |
| SPA-032GY | 32 | 27 | 310 | 6 | 25 |
| SPA-033GY | 33 | 27 | 400 | 6 | 25 |
| SPA-040GY | 40 | 34 | 480 | 5 | 25 |
| SPA-048GY | 48 | 41 | 650 | 5 | 25 |
| SPA-050GY | 50 | 43 | 700 | 5 | 25 |
| SPA-063GY | 63 | 51 | 1025 | 5 | 25 |
| SPA-075GY | 75 | 63 | 1100 | 4 | 25 |
| SPA-090GY | 90 | 80 | 1650 | 3 | 25 |
| SPA-102GY | 102 | 90 | 1700 | 3 | 25 |
| SPA-110GY | 110 | 102 | 1800 | 3 | 25 |

