



## Applications:

Ventilation, suction of erosion materials, scraps powders, agriculture.

## Properties:

Flexible TPU/ PVC hose, reinforced with a heavy duty rigid shock PVC.

Excellent durability to weather conditions and most chemicals. Internally and externally sinuous. Manufactured from material that is approved for contact with food according to European standard

## Standart Colors:

Transparent Green.  
(available in various colors by request)

## Materials:

DOP Free  
RoHS, Reach Standard,  
UV- protections added

## Temperatures Range:

-15°C < Temp < 60 ° C

## Standard:

Tolerance: ISO 1307  
EC food contact (EU)  
10/2011 ,/ 174/2015

Code	Internal Diameter		Weight gr / m ± 10%	Work Pressure Bar 20°C	Vacuum MH <sub>2</sub> O	Bending Radius mm	Roll Length m
	mm	Inch					
VXTPU-012	12	½"	90	2	6	20	30
VXTPU-058	16	5/8"	120	2	6	20	30
VXTPU-034	19	¾"	150	2	6	24	30
VXTPU-078	22	7/8"	165	2	6	33	30
VXTPU-100	25	1"	180	2	6	37	30
VXTPU-130	30		220	2	6	45	30
VXTPU-125	32	1 ¼"	250	2	6	48	30
VXTPU-150	38	1 ½"	330	1	5	57	30
VXTPU-140	40		340	1	5	60	30
VXTPU-148	48		500	1	5	72	30
VXTPU-200	50	2"	500	0.5	5	76	30
VXTPU-260	60		600	0.5	5	90	30
VXTPU-250	63	2 ½"	650	0.5	5	94	30
VXTPU-270	70		710	0.5	5	105	30
VXTPU-300	75	3"	780	0.5	5	114	30
VXTPU-380	80		850	0.5	5	120	30
VXTPU-350	89	3 ½"	1050	0.5	5	133	30
VXTPU-400	102	4"	1250	0.5	5	153	30
VXTPU-450	114	4 ½"	1370	0	5	171	30
VXTPU-500	127	5"	1600	0	5	190	30
VXTPU-600	152	6"	2100	0	5	228	30
VXTPU-660	160		2200	0	5	240	30
VXTPU-670	170		2250	0	5	255	30
VXTPU-700	178	7"	2350	0	5	267	20 / 30
VXTPU-800	203	8"	2700	0	4	304	20 / 30
VXTPU-1000	254	10"	3350	0	4	762	10
VXTPU-1200	305	12"	5000	0	4	915	10

