



Applications:

Ventilation and suction of smoke and dust under hard conditions.

Properties:

Flexible PVC hose, reinforced with a shock resistant rigid PVC spiral.
Excellent durability to weather conditions and most chemicals.
Internally and externally sinuous

Standart Colors:

Transparent White (Available in various colors on request)

Materials:

DOP Free
RoHS, Reach Standard,
UV- protections added

Temperatures Range:

15°C < Temp <60°C

Standard:

Tolerance: ISO 1307

Code	Internal Diameter		Weight gr / m ± 10%	Work Pressure Bar / 20°C	Vacuum MH ₂ O	Bending Radius mm	Roll Length m
	mm	Inch					
VX-100	25	1"	170	2	6	37	30
VX-130	30		230	2	6	45	30
VX-125	32	1 ¼"	240	2	6	48	30
VX-150	38	1 ½"	310	1	5	57	30
VX-200	50	2"	500	0.5	5	76	30
VX-250	63	2 ½"	650	0.5	5	94	30
VX-300	75	3"	780	0.5	5	114	30
VX-400	102	4"	1250	0.5	5	153	30
VX-500	127	5"	1600	0	5	190	30
VX-800	203	8"	2700	0	5	304	20 / 30



sizes are available upon request.

