



Applications

Medium duty hose for transportation of fuel and oil, liquids in the general industrial down to (-40)C.

Properties:

PVC / NBR hose, reinforced with a shock resistant rigid PVC spiral
Excellent resistance to weather conditions and most chemicals.
Resistance to oil & fuel.
Bore smooth to minimize friction loss

Materials:

DOP Free
RoHS, Reach Standard,
UV- protections added
Blend of NBR / PVC compound

Standard Color:

Black

Temperatures Range:

-40°C < Temp <60°C

Standard:

Tolerance: ISO 1307

Code	Internal Diameter		Weight gr / m ± 10%	Work Pressure Bar / 20°C	Vacuum MH ₂ O	Bending Radius mm	Roll Length m
	mm	Inch					
BUNA-034	19	3/4"	300	9	9	100	30/50
BUNA-100	25	1"	360	9	9	120	30/50
BUNA-125	32	1 1/4"	500	8	9	170	30/50
BUNA-150	38	1 1/2"	590	7	9	185	30/50
BUNA-200	50	2"	850	6	9	240	30/50
BUNA-250	63	2 1/2"	1300	6	9	288	30/50
BUNA-300	75	3"	1600	5	9	425	30
BUNA-400	102	4"	2500	3	9	580	30



sizes are available upon request.

