



Applications:

Heavy duty suction and transportation of liquids and food stuff.

Properties:

Flexible PVC hose, reinforced with a shock resistant rigid PVC spiral
 Manufactured from material that is approved for contact with food according to European standard Bore smooth, exterior sinuous

Standard Colors:

Transparent-Red

Materials:

DOP Free
 RoHS, Reach Standard
 UV- protections added

Temperatures Range:

-15°C < Temp <60°C

Standard:

Tolerance: ISO 1307
 EC food contact (EU) 10/2011 ,/ 174/2015

Code	Internal Diameter		Weight gr / m	Work Pressure Bar / 20°C	Bending Radius mm	Roll Length m
	mm	Inch				
NXM-100	25	1"	440	8	150	50
NXM-125	32	1 1/4"	500	8	160	50
NXM-150	38	1 1/2"	700	6	171	50
NXM-140	40		750	6	200	50
NXM-200	51	2"	1000	5	229	50
NXM-260	60		1200	4	270	50
NXM-250	63	2-1/2"	1200	4	270	50
NXM-270	70		1400	4	315	50
NXM-300	76	3"	1600	4	342	50
NXM-350	89	3-1/2"	2100	4	400	30
NXM-400	102	4"	2600	2.5	459	30



sizes are available upon request.

